

C14 CONCRETE SAW

355 mm (14") handheld wet or dry diamond saw with 2800 W motor for up to 125 mm depth of cut. Ideal for indoor cutting.







■ **Dry Cutting With Dust Skid (Optional)**

With spring-loaded suspension for ideal dust containment when dry cutting

Dry cutting dust skid details see P.10



Model	C14
Power Input	2300 W (110-120 V), 2800 W (220 V), 3000 W (230-240 V)
Voltage	220-240 V~ 50-60 Hz or 110-120 V~ 50-60 Hz
No Load RPM	4500/min
Linear speed with 14" blade	54.3 m/s
Blade Diameter	355 mm (14")
Arbor	25.4 mm (1")
Max. Cutting Depth	125 mm (5")
Protection Class	Class I with PRCD
Dimensions (LxWxH)	611 x 245 x 280 mm
Weight	8.0 kg (17.6 lb) 8.4 kg (18.5 lb) with guide rollers
Characteristics / Certification	   

Features

- 1. LED Indicator Indicates load conditions (electronic & thermal protection).
- 2. Integrated water feed system with fine adjustable flow and quick release coupling.
- 3. Tool-free detachable guide rollers for perpendicular cuts and reduced operator fatigue.
- 4. Tool-free detachable splash guard.
- 5. Tool-free blade guard angle adjustment. Handles designed for optimal control.
- 6. Vacuum port for dust or slurry collection with cap.
- 7. Quick removable brush for slurry.
- 8. Externally accessible brushes.

Standard/Optional Accessories See P.20